

SAFETY DATA SHEET

THE DOW CHEMICAL COMPANY*

Product name: ACRYSOL[™] DR-5500 Rheology Modifier

Issue Date: 04/08/2015 Print Date: 01/03/2019

THE DOW CHEMICAL COMPANY* encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: ACRYSOL™ DR-5500 Rheology Modifier

Recommended use of the chemical and restrictions on use Identified uses: This product is used in coatings, textiles, binders and adhesives.

COMPANY IDENTIFICATION

THE DOW CHEMICAL COMPANY* Agent for Rohm and Haas Chemicals LLC 400 ARCOLA ROAD COLLEGEVILLE PA 19426-2914 UNITED STATES

Customer Information Number:

215-592-3000 SDSQuestion@dow.com

EMERGENCY TELEPHONE NUMBER 24-Hour Emergency Contact: 1 800 424 9300 **Local Emergency Contact:** 800-424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

This material is not hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200.

Other hazards

no data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

This product is a mixture.

Component

CASRN

Concentration

Acrylic polymer(s)	Not hazardous	>= 29.0 - <= 31.0 %
Residual monomers	Not available	< 0.05 %
Water	7732-18-5	>= 69.0 - <= 71.0 %

4. FIRST AID MEASURES

Description of first aid measures Inhalation: Move to fresh air.

Skin contact: Wash with water and soap as a precaution. If skin irritation persists, call a physician.

Eye contact: Rinse with plenty of water. If eye irritation persists, consult a specialist.

Ingestion: Drink 1 or 2 glasses of water. Consult a physician if necessary. Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed: Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed Notes to physician: Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIREFIGHTING MEASURES

Suitable extinguishing media: Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media: no data available

Special hazards arising from the substance or mixture Hazardous combustion products: no data available

Unusual Fire and Explosion Hazards: Material can splatter above 100C/212F. Dried product can burn.

Advice for firefighters Fire Fighting Procedures: no data available

Special protective equipment for firefighters: Wear self-contained breathing apparatus and protective suit.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Use personal protective equipment. Keep people away from and upwind of spill/leak. Material can create slippery conditions.

Environmental precautions: CAUTION: Keep spills and cleaning runoff out of municipal sewers and open bodies of water.

Methods and materials for containment and cleaning up: Contain spills immediately with inert materials (e.g., sand, earth). Transfer liquids and solid diking material to separate suitable containers for recovery or disposal.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Keep container tightly closed. Do not breathe vapors, mist or gas.

Conditions for safe storage: Keep from freezing - product stability may be affected. STIR WELL BEFORE USE.

Storage stability

Storage temperature: 1 - 49 °C (34 - 120 °F) Other data: Monomer vapors can be evolved when material is heated during processing operations. See SECTION 8, for types of ventilation required.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits are listed below, if they exist.

Exposure controls

Engineering controls: Use local exhaust ventilation with a minimum capture velocity of 100 ft/min. (0.5 m/sec.) at the point of vapor evolution. Refer to the current edition of Industrial Ventilation: A Manual of Recommended Practice published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

Protective measures: Facilities storing or utilizing this material should be equipped with an eyewash facility.

Individual protection measures

Eye/face protection: Safety glasses with side-shields Eye protection worn must be compatible with respiratory protection system employed.

Skin protection

Hand protection: The glove(s) listed below may provide protection against permeation. (Gloves of other chemically resistant materials may not provide adequate protection): Neoprene gloves

Respiratory protection: A respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements or equivalent must be followed whenever workplace conditions warrant a respirator's use. None required under normal operating conditions. Where vapors and/or mists may occur, wear a properly fitted NIOSH approved (or equivalent) half-mask, air-purifying respirator. Air-purifying respirators should be equipped with NIOSH approved (or equivalent) organic vapor cartridges and N95 filters. If oil mist is present, use R95 or P95 filters.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state	liquid milky	
Color	white	
Odor	no data available	
Odor Threshold	no data available	
рН	2.6 - 3.8	
Melting point/range	0 °C (32 °F) Water	
Freezing point	no data available	
Boiling point (760 mmHg)	100 °C (212 °F) Water	
Flash point	Noncombustible	
Evaporation Rate (Butyl Acetate = 1)	<1.0 Water	
Flammability (solid, gas)	Not Applicable	
Lower explosion limit	Not applicable	
Upper explosion limit	Not applicable	
Vapor Pressure	17 mmHg at 20 °C (68 °F) Water	
Relative Vapor Density (air = 1)	<1.0 Water	
Relative Density (water = 1)	1.0 - 1.2	
Water solubility	Dilutable	
Partition coefficient: n- octanol/water	no data available	
Auto-ignition temperature	no data available	
Decomposition temperature	no data available	
Dynamic Viscosity	no data available	
Kinematic Viscosity	no data available	
Explosive properties	no data available	
Oxidizing properties	no data available	
Molecular weight	no data available	
Percent volatility	69 - 71 % Water	

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: no data available

Chemical stability: Stable

Possibility of hazardous reactions: None known. Product will not undergo polymerization.

Conditions to avoid: no data available

Incompatible materials: There are no known materials which are incompatible with this product.

Hazardous decomposition products: Thermal decomposition may yield acrylic monomers.

11. TOXICOLOGICAL INFORMATION

Toxicological information on this product or its components appear in this section when such data is available.

Acute toxicity

Acute oral toxicity LD50, Rat, > 5,000 mg/kg

Acute dermal toxicity LD50, Rabbit, > 5,000 mg/kg

Acute inhalation toxicity Product test data not available.

Skin corrosion/irritation May cause transient irritation.

Serious eye damage/eye irritation No eye irritation

Sensitization Product test data not available.

Specific Target Organ Systemic Toxicity (Single Exposure) Product test data not available.

Specific Target Organ Systemic Toxicity (Repeated Exposure) Product test data not available.

Carcinogenicity Product test data not available.

Teratogenicity Product test data not available.

Reproductive toxicity Product test data not available.

Mutagenicity Product test data not available.

Aspiration Hazard

Product test data not available.

Additional information

No data are available for this material. The information shown is based on profiles of compositionally similar materials.

COMPONENTS INFLUENCING TOXICOLOGY:

Acrylic polymer(s)

Acute inhalation toxicity The LC50 has not been determined.

Residual monomers

Acute inhalation toxicity The LC50 has not been determined.

12. ECOLOGICAL INFORMATION

Ecotoxicological information on this product or its components appear in this section when such data is available.

General Information

There is no data available for this product.

Toxicity

Acrylic polymer(s) Acute toxicity to fish

No relevant data found.

Residual monomers

Acute toxicity to fish No relevant data found.

Persistence and degradability

Acrylic polymer(s)

Biodegradability: No relevant data found.

Residual monomers

Biodegradability: No relevant data found.

Bioaccumulative potential

Acrylic polymer(s)

Bioaccumulation: No relevant data found.

Residual monomers

Bioaccumulation: No relevant data found.

Mobility in soil

Residual monomers

No relevant data found.

13. DISPOSAL CONSIDERATIONS

Disposal methods: Coagulate the emulsion by the stepwise addition of ferric chloride and lime. Remove the clear supernatant and flush to a chemical sewer. For disposal, incinerate or landfill at a permitted facility in accordance with local, state, and federal regulations.

14. TRANSPORT INFORMATION

DOT

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code Not regulated for transport Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

OSHA Hazard Communication Standard

This product is considered non-hazardous under the OSHA Hazard Communication Standard (29CFR1910.1200).

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

This product is not a hazardous chemical under 29CFR 1910.1200, and therefore is not covered by Title III of SARA.

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This product does not contain a chemical which is listed in Section 313 at or above de minimis concentrations.

Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) Section 103

Releases of this material to air, land, or water are not reportable to the National Response Center under the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) or to state and local emergency planning committees under the Superfund Amendments and Reauthorization Act (SARA) Title III Section 304.

Pennsylvania

Any material listed as "Not Hazardous" in the CAS REG NO. column of SECTION 2, Composition/Information On Ingredients, of this MSDS is a trade secret under the provisions of the Pennsylvania Worker and Community Right-to-Know Act.

California (Proposition 65)

This product contains trace levels of a component or components known to the state of California to cause cancer:

Components	
Ethyl acrylate	

Ethyl acrylate

CASRN 140-88-5

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

16. OTHER INFORMATION

Hazard Rating System

HMIS

2

Health	Flammability	Physical Hazard
1	0	0

Revision

Identification Number: 101168469 / 1001 / Issue Date: 04/08/2015 / Version: 2.0 Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

THE DOW CHEMICAL COMPANY* urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and

understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.