



ROYALE BLACK[®] PP802S

PRODUCT PROFILE

PP802S is a specialty black designed for film and pipe applications. Morphological properties of PP802S are balanced in such a way that it provides a good combination of dispersibility, dilutability, and colour strength.

PP802S is also suitable for PET, PP Fiber and other critical applications where good weathering resistance is desirable.

This grade meets commission Directive EC/10/2011 which deals with plastic materials and articles intended to come in contact with foodstuffs.

TYPICAL VALUE

NSA m ² /g	STSA m ² /g	OAN CC/100g	Tint Strength % ITRB	Sieve Residue 325M, ppm	Heating Loss (As Shipped) %
104	92	99	105	16	0.6

APPLICATION FIELD

TYPICAL APPLICATION	RECOMMENDED DOSAGE
PE Masterbatch	40%
PET Masterbatch	30%

- Recommended dosage can vary depending upon end use and modification of other ingredients
- Packaging - 25kg paper bag or 500/1000kg bulk bag

PCBL Chemical Limited

Registered Office: 31 Netaji Subhas Road, Kolkata - 700 001, WB, India

Corporate Office: RPSG House, 4th Floor, 2/4 Judges Court Road, Kolkata - 700 027, WB, India

P: +91 33 6625 1443 | F: +91 33 2248 0140/2243 6681 | W: www.pcblltd.com | E: pcb.specialtyblack@rpsg.in

Revision No. - 01
Issue - Jan 2025

