



SDS: 0057890
Date Prepared: 10/28/2024

SAFETY DATA SHEET

1. IDENTIFICATION

Product Name: EBECRYL® 4513 radiation curing resins
Synonyms: None
Product Description: unsaturated urethane acrylate resin
Molecular Formula: Mixture
Molecular Weight: Mixture
Intended/Recommended Use: Binder

Allnex USA Inc., 9005 Westside Parkway, Alpharetta, Georgia 30009, USA

For Product and all Non-Emergency Information call your local Allnex contact point or contact us at <http://www.allnex.com/contact>

EMERGENCY PHONE (24 hours/day) - For emergency only involving spill, leak, fire, exposure or accident call:
+1-866-928-0789 (toll free) or +1-215-207-0061 (Carechem 24 - Allnex29003-NCEC)
See Section 16 for Emergency phone numbers for other regions.

Trademarks indicated with ® , TM or * as well as the allnex name and logo are registered, unregistered or pending trademarks of Allnex Netherlands BV or its directly or indirectly affiliated allnex Group companies.

2. HAZARDS IDENTIFICATION

GHS Classification

Aquatic Environment Acute Hazard Category 3
Aquatic Environment Chronic Hazard Category 3

LABEL ELEMENTS

Hazard Statements

Harmful to aquatic life
Harmful to aquatic life with long lasting effects

Precautionary Statements

Avoid release to the environment.
Dispose of contents/container in accordance with local and national regulations.

Hazards Not Otherwise Classified (HNOC), Other Hazards

Not applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS

Component / CAS No.	%	GHS Classification
Urethane acrylate	~ 100	Aquatic Acute 3 (H402) Aquatic Chronic 3 (H412)

The specific chemical identity and/or exact percentage of composition for one or more ingredients has been withheld as a trade secret.

Additional GHS classification or other information may be included in this section but has not been adopted by OSHA. See Section 16 for full text of H phrases.

4. FIRST AID MEASURES

First-aid Measures

Inhalation:

Material is not expected to be harmful if inhaled. Remove to fresh air.

Skin Contact:

Wash immediately with plenty of water and soap.

Eye Contact:

Rinse immediately with plenty of water for at least 15 minutes.

Ingestion:

Material is not expected to be harmful by ingestion. No specific first aid measures are required.

Most Important Symptoms and Effects, Acute and Delayed

None known.

Immediate Medical Attention and Special Treatment

Not applicable.

Notes To Physician:

No specific measures have been identified.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:

Use water spray or fog, carbon dioxide or dry chemical.

Unsuitable Extinguishing Media:

full water jet.

Protective Equipment:

Firefighters, and others exposed, wear self-contained breathing apparatus.

Special Hazards:

Keep containers cool by spraying with water if exposed to fire.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:

Where exposure level is not known, wear approved, positive pressure, self-contained respirator. In addition to the protective clothing/equipment in Section 8 (Exposure Controls/Personal Protection), wear impermeable boots.

Methods For Cleaning Up:

Cover spills with some inert absorbent. Sweep up into containers for disposal. Flush spill area with water.

Environmental Precautions:

Use appropriate containment to avoid environmental contamination. Avoid release to the environment.

References to other sections:

See Sections 7, 8 and 13 for additional information.

7. HANDLING AND STORAGE

HANDLING

Precautions: Avoid release to the environment.

Special Handling Statements: Provide good ventilation of working area (local exhaust ventilation if necessary). During processing and handling of the product, comply with the indicative occupational exposure limit values. Avoid excessive heat, contamination or exposure to direct sunlight to prevent polymerization.

STORAGE

Store in a cool, dry, well ventilated place and keep container tightly closed. Keep away from heat sources and direct sunlight.

Storage Temperature: Store at 4 - 40 °C 39 - 104 °F

Reason: Quality.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Measures:

Engineering controls are not usually necessary if good hygiene practices are followed.

Respiratory Protection:

For operations where inhalation exposure can occur use an approved respirator. Recommendations are listed below. Other protective respiratory equipment may be used based on user's own risk assessment. Recommended respirators include those certified by NIOSH.

Recommended:

Full Face Mask with organic vapor cartridge, Type A filter (BP >65°C)

Eye Protection:

Wear eye/face protection such as chemical splash proof goggles or face shield.

Skin Protection:

Avoid skin contact. Wear impermeable gloves.

Hand Protection:

Wear protective gloves. Recommendations are listed below. Other protective materials may be used based on user's own risk assessment. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred. Replace gloves immediately when torn or any change in appearance (dimension, color, flexibility etc.) is noticed.

Gloves for repeated or prolonged exposure - non exhaustive list:

Nitrile rubber (NBR), thickness: > 0.56 mm, break through time: up to 480 min

Gloves for short term exposure/splash protection - non exhaustive list:
Nitrile rubber (NBR), thickness: 0.1 mm, break through time: up to 30 min

The chemical resistance depends on the type of product and amount of product on the glove. Therefore gloves need to be changed when in contact with chemicals.

Not suitable gloves - non exhaustive list:
Latex gloves

Due to many conditions (e.g. temperature, abrasion) the practical usage of a chemical protective glove in practice may be much shorter than the permeation time determined through testing.

Additional Advice:

Before eating, drinking, or smoking, wash face and hands thoroughly with soap and water.

Exposure Limit(s)

No values have been established.

Biological Exposure Limit(s)

No values have been established.

9. PHYSICAL AND CHEMICAL PROPERTIES

Color:	yellowish
Appearance:	liquid
Odor:	slight
Boiling Point:	> 250 °C 482 °F @ 1.013 hPa DIN 53171
Melting Point:	Not available
Vapor Pressure:	6 hPa @ 20 °C EG A4
Specific Gravity/Density:	~ 1.15 g/cm ³ DIN 51757 @ 20 °C
Vapor Density:	Not available
Percent Volatile (% by wt.):	Not available
pH:	Not applicable
Saturation In Air (% By Vol.):	Not applicable
Evaporation Rate:	Non-volatile
Solubility In Water:	@ 15 °C immiscible
Volatile Organic Content:	Not available
Flash Point:	~ 149 °C 300 °F @ 1.013 hPa DIN EN ISO 2719
Flammable Limits (% By Vol):	Not applicable
Autoignition Temperature:	Not available
Decomposition Temperature:	Not available
Partition coefficient n-octanol/water (log value):	Not available
Odor Threshold:	Not available
Viscosity (Kinematic):	Not applicable
Viscosity (Dynamic):	~ 25000 mPa.s @ 23 °C DIN EN ISO 3219
Flammability:	Normal combustion
Oxidizing Properties:	No

Other safety characteristics

Self-accelerating polymerisation temperature (SAPT):

According to special provision SP386, it is ensured that the level of chemical stabilization is sufficient to prevent

dangerous polymerization during the entire duration of transport.

10. STABILITY AND REACTIVITY

Reactivity:	No information available
Stability:	Stable.
Conditions To Avoid:	Avoid direct exposure to sunlight. Avoid temperatures above 60°C (140°F). Avoid friction with temperature increase as result. Avoid exposure to strong UV sources. Avoid direct contact with heat sources. Prevent loss of dissolved oxygen.
Polymerization:	May occur
Conditions To Avoid:	Uncontrolled polymerization may cause rapid evolution of heat and increase in pressure that could result in violent rupture of sealed storage vessels or containers. Hazardous polymerization can occur when exposed to direct sunlight. Hazardous exothermic polymerization can occur when heated. Avoid contact with bases or amines. Avoid contact with strong oxidizing agents. Avoid contact with free radical initiators. Avoid loss of dissolved oxygen.
Materials To Avoid:	Avoid contact with peroxides. Copper, copper alloys, carbon steel, iron and rust. Avoid free radical producing initiators. Contact with alkalis. They give an exothermic reaction with the product. Unintentional contact with them should be avoided. Avoid contact with active metals.
Hazardous Decomposition Products:	No hazardous decomposition products if stored and handled as prescribed. soot when burned incompletely burned carbon compounds oxides of carbon and/or nitrogen

11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Skin, Eyes, Oral.

Acute toxicity - oral: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

Acute toxicity - dermal: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

Acute toxicity - inhalation: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

Skin corrosion / irritation: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

Serious eye damage / eye irritation: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

Respiratory sensitization: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

Skin sensitization: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

Carcinogenicity: Not Classified - Based on available data and/or professional judgment, the classification

criteria are not met.

Germ cell mutagenicity: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

Reproductive toxicity: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

Specific target organ toxicity (STOT) - single exposure: Not Classified. - Based on available data and/or professional judgment, the classification criteria are not met.

Specific target organ toxicity (STOT) - repeated exposure: Not Classified. - Based on available data and/or professional judgment, the classification criteria are not met.

Aspiration hazard: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

PRODUCT TOXICITY INFORMATION

ACUTE TOXICITY DATA

oral	rat	Acute LD50	> 2000 mg/kg Toxicological studies of a comparable product.
dermal	rabbit	Acute LD50	> 2000 mg/kg (estimated)
Inhalation	rat	Acute LC50 4 hr	> 5 mg/l (Dust/Mist) estimated

LOCAL EFFECTS ON SKIN AND EYE

Acute Irritation	dermal	rabbit	Not irritating
Acute Irritation	eye	rabbit	Not irritating

ALLERGIC SENSITIZATION

Sensitization	Skin	mouse	Not sensitizing
Sensitization	respiratory	No data	

SUBACUTE/SUBCHRONIC TOXICITY

oral (gavage)	rat	No data
dermal	rat	No data

GENOTOXICITY

Assays for Gene Mutations

Ames Salmonella Assay	No data
-----------------------	---------

OTHER INFORMATION

The toxicological properties of this material have not been fully determined.

HAZARDOUS INGREDIENT TOXICITY DATA

Based on toxicological studies of a similar substance the urethane acrylate has an acute oral LD50 (rat) of > 2000 mg/kg. Direct contact may cause slight eye irritation (rabbits). The substance is not irritating to the skin (rabbits) and did not show a sensitizing effect on mouse.

12. ECOLOGICAL INFORMATION

TOXICITY, PERSISTENCE AND DEGRADABILITY, BIOACCUMULATIVE POTENTIAL, MOBILITY IN SOIL, OTHER ADVERSE EFFECTS

Overall Environmental Toxicity: Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

The ecological assessment for this material is based on an evaluation of its components.

ECOTOXICITY**ALGAE TEST RESULTS**

Test: Growth Inhibition (OECD 201)

Duration: 72 hr

Species: Green Algae (*Scenedesmus subspicatus*)

381.2 mg/l IC50

FISH TEST RESULTS

Test: Acute toxicity, freshwater (OECD 203)

Duration: 96 hr.

Species: Zebra Fish (*Brachydanio rerio*)

67.9 mg/l LC50

INVERTEBRATE TEST RESULTS

Test: Acute Immobilization (OECD 202)

Duration: 48 hr

Species: Water Flea (*Daphnia magna*)

46.5 mg/l EC50

PERSISTENCE AND DEGRADABILITY**DEGRADATION**

Test: Biodegradability

This material is not readily biodegradable. Information based on a structurally similar material

RESULTS OF PBT AND vPvB ASSESSMENT

Not determined

HAZARDOUS INGREDIENT TOXICITY DATA

Component / CAS No.	Toxicity to Fish
Urethane acrylate (-)	LC50 67.9 mg/L - Zebra Fish (<i>Brachydanio rerio</i>) (96h)

Component / CAS No.	Toxicity to Water Flea
Urethane acrylate (-)	EC50 46.5 mg/L - Water Flea (<i>Daphnia magna</i>) (48h)

Component / CAS No.	Toxicity to Algae
Urethane acrylate (-)	IC50 381.2 mg/L - Green Algae (<i>Scenedesmus subspicatus</i>) (72h)

Component / CAS No.	Partition coefficient
Urethane acrylate (-)	Not available

13. DISPOSAL CONSIDERATIONS

The information on RCRA waste classification and disposal methodology provided below applies only to the product, as supplied. If the material has been altered or contaminated, or it has exceeded its recommended shelf life, the guidance may be inapplicable. Hazardous waste classification under federal regulations (40 CFR Part 261 et seq) is dependent upon whether a material is a RCRA "listed hazardous waste" or has any of the four RCRA "hazardous waste characteristics." Refer to 40 CFR Part 261.33 to determine if a given material to be disposed of is a RCRA "listed hazardous waste"; information contained in Section 15 of this SDS is not intended to indicate if the product is a "listed hazardous waste." RCRA Hazardous Waste Characteristics: There are four characteristics defined in 40 CFR Section 261.21-61.24: Ignitability, Corrosivity, Reactivity, and Toxicity. To determine Ignitability, see Section 9 of this SDS (flash point). For Corrosivity, see Sections 9 and 14 (pH and DOT corrosivity). For Reactivity, see Section 10 (incompatible materials). For Toxicity, see Section 3 (composition). Federal regulations are subject to change. State and local requirements, which may differ from or be more stringent than the federal regulations, may also apply to the classification of the material if it is to be disposed. The Company encourages the recycle, recovery and reuse of materials, where permitted, as an alternate to disposal as a waste. The Company recommends that organic materials classified as RCRA hazardous wastes be disposed of by thermal treatment or incineration at EPA approved facilities. The Company has provided the foregoing for information only; the person generating the waste is responsible for determining the waste classification and disposal method.

14. TRANSPORT INFORMATION

This section provides basic shipping classification information. Refer to appropriate transportation regulations for specific requirements.

US DOT

Dangerous Goods? Not applicable/Not regulated

TRANSPORT CANADA

Dangerous Goods? Not applicable/Not regulated

ICAO / IATA

Dangerous Goods? Not applicable/Not regulated

IMO

Dangerous Goods? Not applicable/Not regulated

SPECIAL PRECAUTIONS FOR USER

Protect against external heat sources higher than +40°C/104°F.

15. REGULATORY INFORMATION

Inventory Information

United States (USA): All components of this product are designated as "Active" on the TSCA Inventory or are not required to be listed.

Canada: One or more components of this product are NOT included on the Canadian Domestic Substances List (DSL).

European Economic Area (including EU): When purchased and shipped from an Allnex legal entity based in the EEA (EU or Norway), this product is compliant with the registration of the REACH Regulation (EC) No. 1907/2006 as all its components are either excluded, exempt and/or registered.

Australia: One or more components of this product have NOT yet been included in the Australian Inventory of Industrial Chemicals (AIIC) or assessed by AICIS.

New Zealand: This product is NOT approved under the Hazardous Substances and New Organisms (HSNO) Act.

China: One or more components of this product are NOT included on the Chinese (IECSC) inventory. The company has obtained the required notification approvals from the Ministry of Environmental Protection (MEP) as per the "Environmental Administrative Measures for New Chemical Substance" for the component(s) not listed in the Chinese Inventory (IECSC). The product can be imported/manufactured in China ONLY under specific conditions.

Japan: All components of this product are included on the Japanese (ENCS and ISHL) inventories or are not required to be listed on the Japanese inventories.

Korea: All components of this product are included on the Korean (ECL) inventory or are not required to be listed on the Korean inventory. When purchased from Allnex Korea or Chemart distributor this product is compliant with the ARECs (the Act on the Registration and Evaluation, etc. of Chemical Substances). All its components are either excluded, exempt, pre-notified and/or registered. When purchased from another allnex entity, please contact PSRA-KREACH@allnex.com to check the possibility to be covered by our Only Representative.

Philippines: One or more components of this product are NOT included on the Philippine (PICCS) inventory.

Taiwan: All components of this product are included in the Taiwan chemical substance inventory or are not required to be listed on the Taiwan chemical substance inventory (TCSI).

Switzerland: All components of this product are exempt from the new substance notification requirements for Switzerland (SR 813.11 art. 24-26).

OTHER ENVIRONMENTAL INFORMATION

The following components of this product may be subject to reporting requirements pursuant to Section 313 of CERCLA (40 CFR 372), Section 12(b) of TSCA, or may be subject to release reporting requirements (40 CFR 307, 40 CFR 311, etc.) See Section 13 for information on waste classification and waste disposal of this product.

This product does not contain any components regulated under these sections of the EPA

PRODUCT HAZARD CATEGORY UNDER SECTIONS 311 AND 312 OF EPCRA

Physical Hazards

Not applicable

Health Hazards

Not applicable

16. OTHER INFORMATION

NFPA Hazard Rating (National Fire Protection Association)

Health: 1 - Materials that, under emergency conditions, can cause significant irritation.

Fire: 1 - Materials that must be preheated before ignition can occur.

Instability: 1 - Materials that in themselves are normally stable, but that can become unstable at elevated temperatures and pressures.

Reasons for Issue: Revised Section 1

Date Prepared: 10/28/2024

Date of last significant revision: 03/06/2022

Component - Hazard Statements

Urethane acrylate

H402 - Harmful to aquatic life.

H412 - Harmful to aquatic life with long lasting effects.

Emergency phone numbers for other regions

Asia Pacific

Australia: +61 1800 022 037 (Allnex Australia)

China (PRC): +86 532 8388 9090 (NRCC)

India: 000 800 100 7479 (toll free) or +65 3158 1198 (Carechem 24)

Indonesia: 007 803 011 0293 (Carechem 24)

Japan: 0120 015 230 (toll free) (Carechem 24)

Korea: +82 2 3479 8401 (Carechem 24)

Malaysia: +60 3 6207 4347 (Carechem 24)

New Zealand: +64 0800 803 002 (Allnex New Zealand)

Philippines: +63 2 231 2149 (Carechem 24)

Taiwan: +886 2 8793 3212 (Carechem 24)

Vietnam: +84 8 4458 2388 (Carechem 24)

All Others: +65 3158 1074 (Carechem 24)

Europe

+44 (0) 1235 239 670 (Carechem 24)

Middle East, Africa

+44 (0) 1235 239 671 (Carechem 24)

Latin America

Brazil: +55-800-707-7022 (toll free) or +55-11-98149-0850 (Suatrans 24)

Chile: +56 2 2582 9336 (Carechem 24)

Mexico and all others: +52-555-004-8763 (Carechem 24)

Canada

+1-800-579-7421 (toll free) or +1-215-207-0061 (Carechem 24)

Prepared By: Product Sustainability & Regulatory Affairs Department, <http://www.allnex.com/contact>

This information is given without any warranty or representation. We do not assume any legal responsibility for same, nor do we give permission, inducement, or recommendation to practice any patented invention without a license. It is offered solely for your consideration, investigation, and verification. Before using any product, read its label.
