



SAFETY DATA SHEET

BLUE CUBE OPERATIONS LLC

Product name: D.E.R.™ 732 Epoxy Resin

Issue Date: 03-28-2019

Print Date: 06-09-2021

BLUE CUBE OPERATIONS LLC encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: D.E.R.™ 732 Epoxy Resin

Recommended use of the chemical and restrictions on use

Identified uses: Used in applications such as: Automotive coatings. Casting. Civil engineering. Tooling. Marine and protective coatings. Adhesives. Potting and encapsulation.

COMPANY IDENTIFICATION

BLUE CUBE OPERATIONS LLC
190 CARONDELET PLAZA, SUITE 1530
CLAYTON
MO
US
63105-3467

Customer Information Number:

+18442383445
INFO@OLIN.COM

EMERGENCY TELEPHONE

24-Hour Emergency Contact: +1 800 424 9300

Local Emergency Contact: 800-424-9300/703-741-5970

2. HAZARDS IDENTIFICATION

Hazard classification

This material is not hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200.

Other hazards

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms: Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(oxiranylmethyl)-.omega.-(oxiranylmethoxy)-
This product is a substance.

Component

CASRN

Concentration

Polypropylene glycol diepoxide resin

26142-30-3

100.0%

4. FIRST AID MEASURES

Description of first aid measures

General advice: If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air; if effects occur, consult a physician.

Skin contact: Wash off with plenty of water.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

Ingestion: If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

Most important symptoms and effects, both acute and delayed: Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIREFIGHTING MEASURES

Suitable extinguishing media: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective. Water fog, applied gently may be used as a blanket for fire extinguishment.

Unsuitable extinguishing media: Do not use direct water stream. May spread fire.

Special hazards arising from the substance or mixture

Hazardous combustion products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Phenolic compounds. Carbon monoxide. Carbon dioxide.

Unusual Fire and Explosion Hazards: Violent steam generation or eruption may occur upon application of direct water stream to hot liquids. Dense smoke is emitted when burned without sufficient oxygen.

Advice for firefighters

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Do not use direct water stream. May spread fire. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Water fog, applied gently may be used as a blanket for fire extinguishment.

Special protective equipment for firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Keep unnecessary and unprotected personnel from entering the area. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Environmental precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Methods and materials for containment and cleaning up: Contain spilled material if possible. Collect in suitable and properly labeled open containers. Absorb with materials such as: Sand. Remove residual with soap and hot water. Residual can be removed with solvent. Solvents are not recommended for clean-up unless the recommended exposure guidelines and safe handling practices for the specific solvent are followed. Consult appropriate solvent Safety Data Sheet for handling information and exposure guidelines. See Section 13, Disposal Considerations, for additional information.

7. HANDLING AND STORAGE

Precautions for safe handling: See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Conditions for safe storage: Additional storage and handling information on this product may be obtained by calling your sales or customer service contact.

Storage stability

Storage temperature:	Shelf life: Use within
2 - 43 °C (36 - 109 °F)	24 Month

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits are listed below, if they exist.

Exposure limits have not been established for those substances listed in the composition, if any have been disclosed.

Exposure controls

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use safety glasses (with side shields). If exposure causes eye discomfort, use a full-face respirator.

Skin protection

Hand protection: Chemical protective gloves should not be needed when handling this material. Consistent with general hygienic practice for any material, skin contact should be minimized.

Other protection: No precautions other than clean body-covering clothing should be needed.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions, no respiratory protection should be needed; however, if handling at elevated temperatures without sufficient ventilation, use an approved air-purifying respirator.

The following should be effective types of air-purifying respirators: Organic vapor cartridge.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state	Liquid.
Color	Colorless
Odor	Ether
Odor Threshold	No test data available
pH	Not applicable
Melting point/range	Not applicable
Freezing point	Not determined
Boiling point (760 mmHg)	≥ 200 °C (≥ 392 °F) at 760 mmHg <i>Literature</i>
Flash point	closed cup 148 °C (298 °F) <i>Pensky-Martens Closed Cup ASTM D 93</i>
Evaporation Rate (Butyl Acetate = 1)	No test data available
Flammability (solid, gas)	Not Applicable
Lower explosion limit	Not determined
Upper explosion limit	Not determined
Vapor Pressure	1.4 mmHg at 80 °C (176 °F) <i>Literature</i>
Relative Vapor Density (air = 1)	Not determined
Relative Density (water = 1)	1.06 <i>Literature</i>
Water solubility	7.8 % <i>Literature</i>
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	Not determined

Decomposition temperature	No test data available
Dynamic Viscosity	60 - 70 cP at 25 °C (77 °F) ASTM D 445
Kinematic Viscosity	No test data available
Explosive properties	No data available
Oxidizing properties	No data available
Molecular weight	Not determined
Percent volatility	Not determined

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: No data available

Chemical stability: Stable under recommended storage conditions. See Storage, Section 7.

Possibility of hazardous reactions: Will not occur by itself. Masses of more than one pound (0.5 kg) of product plus an aliphatic amine will cause irreversible polymerization with considerable heat build-up.

Conditions to avoid: Exposure to elevated temperatures can cause product to decompose.

Incompatible materials: Avoid contact with oxidizing materials. Avoid contact with: Acids. Bases. Avoid unintended contact with amines.

Hazardous decomposition products: Decomposition products depend upon temperature, air supply and the presence of other materials. Uncontrolled exothermic reaction of epoxy resins release phenolics, carbon monoxide, and water.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Acute toxicity

Acute oral toxicity

Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury.

LD50, Rat, > 2,000 mg/kg OECD Test Guideline 401 No deaths occurred at this concentration.

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

LD50, Rat, male and female, > 2,000 mg/kg OECD Test Guideline 402 No deaths occurred at this concentration.

Acute inhalation toxicity

At room temperature, exposure to vapor is minimal due to low volatility. Vapor from heated material, mist or aerosols may cause respiratory irritation.
The LC50 has not been determined.

Skin corrosion/irritation

Essentially nonirritating to skin.

Serious eye damage/eye irritation

May cause slight temporary eye irritation.
Elevated temperatures may generate vapor levels sufficient to cause eye irritation. Effects may include discomfort and redness.

Sensitization

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:
Relevant data not available.

Specific Target Organ Systemic Toxicity (Single Exposure)

Available data are inadequate to determine single exposure specific target organ toxicity.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

No relevant data found.

Carcinogenicity

Based on information for component(s): Many studies have been conducted to assess the potential carcinogenicity of diglycidyl ether of bisphenol A (DGEBA). Indeed, the most recent review of the available data by the International Agency for Research on Cancer (IARC) has concluded that DGEBA is not classified as a carcinogen. Although some weak evidence of carcinogenicity has been reported in animals, when all of the data are considered, the weight of evidence does not show that DGEBA is carcinogenic.

Teratogenicity

No relevant data found.

Reproductive toxicity

No relevant data found.

Mutagenicity

No relevant data found.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

COMPONENTS INFLUENCING TOXICOLOGY:

Polypropylene glycol diepoxide resin

Acute inhalation toxicity

The LC50 has not been determined.

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Toxicity

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

LC50, Leuciscus idus (Golden orfe), 96 Hour, 160 mg/l

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 48 Hour, 220 mg/l

Persistence and degradability

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

10-day Window: Fail

Biodegradation: 14 - 21 %

Exposure time: 28 d

Method: OECD Test Guideline 301B or Equivalent

Bioaccumulative potential

Bioaccumulation: No relevant data found.

Mobility in soil

No relevant data found.

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device.

14. TRANSPORT INFORMATION

DOT

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

Not regulated for transport
Consult IMO regulations before transporting ocean bulk

Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code

Classification for AIR transport (IATA/ICAO):

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

OSHA Hazard Communication Standard

This product is not a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

This product is not a hazardous chemical under 29CFR 1910.1200, and therefore is not covered by Title III of SARA.

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Pennsylvania Worker and Community Right-To-Know Act:

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)

This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

16. OTHER INFORMATION

Hazard Rating System**NFPA**

Health	Fire	Reactivity
1	1	0

Revision

Identification Number: 101201597 / 1015 / Issue Date: 03-28-2019 / Version: 5.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

BLUE CUBE OPERATIONS LLC urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.