



ROYALE BLACK[®] PP803K

PRODUCT PROFILE

PP803K is primarily designed for all kind of film applications meeting stringent requirements of film dispersion. It has moderate jetness and low particle size to give adequate opacity and UV resistance.

PP803K is also suitable for pipe application

This grade also meets commission Directive EC/10/2011 which deals with plastic materials and articles intended to come in contact with foodstuffs.

TYPICAL VALUE

NSA m ² /g	STSA m ² /g	OAN CC/100g	Tint Strength % ITRB	Sieve Residue 325M, ppm	Heating Loss (As Shipped) %
89	85	100	103	13	0.6

APPLICATION FIELD

TYPICAL APPLICATION	RECOMMENDED DOSAGE
PE Masterbatch	40%

- Recommended dosage can vary depending upon end use and modification of other ingredients
- Packaging - 25kg paper bag or 500/1000kg bulk bag

PCBL Chemical Limited

Registered Office: 31 Netaji Subhas Road, Kolkata - 700 001, WB, India

Corporate Office: RPSG House, 4th Floor, 2/4 Judges Court Road, Kolkata - 700 027, WB, India

P: +91 33 6625 1443 | F: +91 33 2248 0140/2243 6681 | W: www.pcbltd.com | E: pcbl.specialtyblack@rpsg.in

Revision No. - 01
Issue - Jan 2025

