

This SDS complies with OSHA HazCom Standard 29 CFR 1910.1200 (GHS), Canadian Workplace Hazardous Material Information System (WHMIS), Mexico NOM-018-STPS-2015

# SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

#### 1.1 Identification

Product Form: Mixture

Chemical Name: Magnesium Silicate Hydrate

Product Name(s):

Flextalc Series: Nanoflex, Nanoflex-D, Performaflex-A, Performaflex D, Performaflex-AD, 610/612D,

815/815D. Clear-Bloc Series: 100, 100-S, C(D), 80, 80-S

Cimtuff Series: 9102, 9103W, 9103, 9103-S, 9103-C, 9107, 9110, 9115 Cimtalc Series: 2, 3, 3-S, 3-C, 7, 10, 15; 8803; 8807; 8810; 8815

CimCoat Series: 1050, 3040, QD3040, 4025

RP Series: 9310, 9305, 9410, 9405

Aspect Series: Aspect 3, Aspect 7, Aspect 10, Aspect 15

Other: SAS

### 1.2 Relevant Identified Uses of the Substance or Mixture and Uses Advised Against:

Use of Substance/Mixture: Mineral additive for use in paper, paints, ceramics, plastics, personal care, etc.

### 1.3 Details of the Supplier of the Safety Data Sheet:

Manufacturer Information (Corporate):

CIMBAR Performance Minerals Phone Number: 1-800-852-6868

104 North 3<sup>rd</sup> Avenue Fax Number: 1-706-517-0516

Chatsworth, Ga. 30705

# **SECTION 2 - HAZARDS IDENTIFICATION**

# 2.1 Classification of the Substance/Mixture

GHS-US Classification: Category 2 Carcinogen

#### 2.2 Label Elements:

GHS-US Labeling:



GHS- US Hazard Statements: H350 May cause cancer

# 2.3 Other Hazards

Other Hazards not contributing to the classification: Prolonged and/or massive exposure to respirable crystalline silicacontaining dust may cause silicosis, a nodular pulmonary fibrosis caused by deposition in the lungs of fine respirable particles of crystalline silica. 2009 IARC review of crystalline silica found that the polymorph type and specific exposure scenarios may lead to higher risk of chronic illnesses.

### 2.4 Unknown Acute Toxicity (GHS-US)

Not applicable.

SDS-TALC Page 1 of 8

Revision: 20 (09/20/2025)



# SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

#### 3.1 Substance

Not applicable

#### 3.2 Mixture:

MIXIUIC.				
Component	CAS Number	Composition %	EC Number	Classification
Talc (magnesium silicate hydrate)	14807-96-6	>95	238-877-9	NONE
Quartz	14808-60-7	<0.2	238-878-4	NONE

Full text of hazard classes and H-statements: see Section 16

### **SECTION 4 - FIRST AID MEASURES**

# 4.1 Description of first aid measures:

First-aid measures general:

Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice,

show the label where possible.

Inhalation:

Move person to non-contaminated air. If symptoms develop, obtain medical attention.

Skin Contact:

Remove affected clothing and wash the exposed skin area with mild soap and water, followed by

warm water rinse. If symptoms develop, obtain medical attention.

Eye Contact

In case of contact with eyes, rinse immediately with plenty of water for several minutes.

Ingestion

Drink plenty of water. Never give liquid to an unconscious person

# 4.2 Most Important Symptoms and Effects, both Acute and Delayed:

After Inhalation:

May cause irritation to the respiratory tract.

After Skin Contact:

Repeated and/or prolonged exposure skin contact may cause irritation.

After Eye Contact:

May cause eye irritation.

### 4.3 Indication of any immediate medical attention and special treatment:

No additional information available.

### **SECTION 5 - FIRE FIGHTING MEASURES**

### 5.1 Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire. Unsuitable Extinguishing Media: None known.

### 5.2 Special Hazards arising from the substance or mixture

Fire Hazard: None known.

Reactivity: Stable under normal conditions.

### 5.3 Advice for Firefighters

Protection during Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection (N95 minimum).

SDS-TALC Page 2 of 8

Revision: 20 (09/20/2025)



# SECTION 6 - ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, personal protective equipment (PPE) and emergency procedures:

Use proper PPE. NIOSH approved respirators are recommended. Spilled materials may cause slippery conditions when wet. Care should be taken when walking on spills on floor or concrete pads.

# 6.1.1 For non-emergency personnel

Protective Equipment: Use personal protective equipment as required.

Emergency Procedure: Evacuate unnecessary personnel. Avoid dust formation. Avoid contact with skin and eyes. Do not breathe dust.

# 6.1.2 For emergency responders

Protective Equipment: Wear suitable protective clothing, gloves, eye or face protection. Where excessive dust may result, wear approved dust respirator.

Emergency Procedures: Ensure adequate ventilation. Avoid dust formation. Avoid contact with skin and eyes. Do not breathe dust. Wear independent breathing equipment.

#### 6.2 Environmental Precautions

Notify authorities if large amounts of the product enter sewers or public waters.

### 6.3 Methods and material for containment and cleanup

Dry product should be cleaned with a shovel or vacuum cleaning system while wearing the PPE described above. Do not discharge into drains or water contributories. Washing the floor with water is NOT recommended since it may cause slippery conditions. If the floor is already wet, and only in this case, the floor should be thoroughly flushed with water to remove the slippery conditions.

### 6.4 Reference to other sections

Section 8: Exposure controls/personal protection.

Section 13: Disposal considerations.

# SECTION 7 - HANDLING AND STORAGE

#### 7.1 Precautions for safe handling:

Minimize dust generation and assimilation. If excessive dust is generated, provide adequate ventilation, and use proper personal protective equipment.

#### 7.2 Conditions for safe storage:

Keep the product dry and in closed containers. Store it in a cool and well-ventilated area.

# SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters:

Talc (14807-96-6)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
OSHA	OSHA PEL (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> Respirable Fraction
OSHA	Remark (OSHA)	(3) see Table Z-3

Quartz (fine fraction) 14808-60-7		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> Respirable Fraction
OSHA	OSHA PEL	0.1 mg/m <sup>3</sup>
OSHA	Remark (OSHA)	(3) see Table Z-3

SDS-TALC Page 3 of 8

Revision: 20(09/20/2025)



#### **8.2 Exposure Controls**

Appropriate engineering controls: Use exhaust ventilation, if possible, to reduce the dust concentration to recommended exposure limits.

Personal Protective Equipment: Avoid unnecessary exposure.

Eye Protection: Wear side shield safety glasses or goggles.

Hand Protection- Rubber gloves are recommended for prolonged exposure.

Respiratory Protection- Use NIOSH approved dust respirators.

Other Information: Do not eat, drink, or smoke during use.

# SECTION 9 - PHYSICAL & CHEMICAL PROPERTIES

9.1 Appearance:	White, tan or light grey powder.
9.2 Odor:	Odorless
9.3 pH:	8.5-9.5 (10% Solution)
9.4 Melting Point:	>1300° C
9.5 Flammability (solid, gas):	Not flammable
9.6 Upper/Lower Flammability or Explosive Limits:	Not explosive. Limits not applicable.
9.7 Relative Density:	2.58-2.83 g/cm <sup>3</sup>
9.8 Solubility: Solubility in water	Negligible Yes
Solubility in hydrofluoric acid	
9.9 Decomposition Temperature:	>1000° C
9.10 Explosive Properties:	Not explosive
9.11 Oxidizing Properties:	Non-oxidizing

# SECTION 10 - STABILITY & REACTIVITY

10.1 Reactivity: Stable under normal conditions.

10.2 Chemical Stability: Stable under normal conditions.

10.3 Possibility of Hazardous Reactions: Noneknown.

10.4 Conditions to Avoid: Dust formation.

10.5 Incompatible Materials: None.

10.6 Hazardous Decomposition Products: None known.

# **SECTION 11 - TOXICOLOGICAL INFORMATION**

# 11.1 Information on Toxicological Effects:

Acute Toxicity: Not classified.

Skin Corrosion/Irritation: Not classified. Serious Eye Damage/Irritation: Not

classified.

Respiratory or Skin Sensitization: Not classified.

Germ Cell Mutagenicity: Not classified.

Carcinogenic Status: May cause cancer (Inhalation) under certain conditions.

Talc (14807-96-6)	
IARC Group	Category 2

SDS-TALC Page 4 of 8

Revision: 20(09/20/2025)



# SAFFTY DATA SHFFT

National Toxicology	Not listed by NTP, ACGIH, OSHA, or NIOSH
Program (NTP) Status	

Reproductive Toxicity: Not classified.

Specific Target Organ Toxicity (single exposure): Not classified. Specific Target Organ Toxicity (repeated exposure: Not classified.

Aspiration Hazard: Not classified.

Symptoms/Injuries After Inhalation: May cause irritation to respiratory tract.

Symptoms/Injuries after skin contact: Repeated and/or prolonged skin contact may cause irritation.

# SECTION 12 - ECOLOGICAL INFORMATION

12.1 Toxicity Ecology- General: Not classified.

Talc (14807-96-6) LC50 Fish >100 g/l Brach danio rerio

Persistence and Degradability 12.2

-		
	Talc (14807-96-6)	
	Persistence and Degradability	Not relevant for inorganic substances

12.3 **Bio-accumulative Potential** 

4	o-accamalative i otential	
	Talc (14807-96-6)	
	Bio-accumulative Potential	Not relevant for inorganic substances

Mobility in Soil

Talc (14807-96-6)	
Ecology-Soil	No information available

12.5 Other adverse effects: No specific adverse effects known.

# **SECTION 13 - DISPOSAL CONSIDERATIONS**

#### **Waste Treatment Methods:** 13.1

Talc is not considered a hazardous waste as defined by the US EPA RCRA (40 CFR 261) regulations. Observe all applicable federal, state and local regulations when handling, storing or disposing of this substance.

#### 13.2 Disposal of Packaging:

Where possible, recycling is preferable to disposal. Recycling and disposal of packaging should be done by an authorized waste management company in compliance with local regulations. Responsibility for proper waste disposal lies with the waste owner.

# **SECTION 14 - TRANSPORT INFORMATION**

- 14.1 US Department of Transportation (DOT): Not regulated.
- 14.2 Canadian Transportation of Dangerous Goods: Not regulated.
- 14.3 Land Transport- ADR/RID: Not regulated.
- 14.4 Air Transport- IATA/ICAO: Not regulated.
- Maritime Transport- IMDG: Not regulated. 14.5
- Harmonized Tariff Code: Talc- crushed or powdered. 2526.20.00.
- EPA TSCA 12(B) Export Notification: Not regulated. 14.7

Page **5** of **8** Revision: 20(09/20/2025)

SDS-TALC



# **SECTION 15 - REGULATORY INFORMATION**

# 15.1 <u>US Federal Regulations</u>

This product or mixture does not contain a toxic or chemicals is excess of the applicable minimal concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Talc (14807-96-6)	
Taic (1 <del>1</del> 007-30-0)	
Listed on the United States TSCA	(Toxic Substances Control Act) Inventory
Listed on the Officed States 13CA	( TOXIC Substances Control Act) inventory

Quartz (fine fraction) (14808-60-7) Listed on the United States TSCA (Toxic Substances Control Act) Inventory

# 15.2 US State Regulations

California Proposition 65: WARNING- This product can expose you to chemicals including silica, crystalline, which is known in the state of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

Quartz (fine fraction) (14808-96-6)			
US-California-Prop 65- Carcinogens List	US- California- Prop 65- Developmental Toxicity	US- California- Prop 65- Reproductive Toxicity (Female)	US- California- Prop 65- Reproductive Toxicity (Male)
Yes	Yes	Yes	No

# TALC (14807-96-6)

New Jersey- Right to Know Hazardous Substance List Pennsylvania- Right to

Massachusetts- Right to Know List

# Quartz (14808-60-7)

New Jersey- Right to Know Hazardous

Substance List Pennsylvania- Right to

Know List

Massachusetts- Right to Know List

### **International Regulations:**

#### Canada

TALC	
WHMIS Classification	Class D Division 2 Subdivision 2- Very toxic material causing other toxic effects

SDS-TALC Page 6 of 8

Revision: 20 (09/20/2025)



# SAFFTY DATA SHFFT

EU Regulations: No additional information available National Regulations

All naturally occurring components of this product are automatically included in the US-EPA TSCA inventory list per 4- CFR 710.4(b). All other components are on the US-EPA TSCA inventory list. Generally acceptable for use in vanilla powder and vanilla-vanillin powder under food standards 21 CFR 169.179 and 169-182.

-Generally approved for use as a colorant only as components of paper and paperboard in contact with aqueous fatty foods (21 CFR 176.170).

-Generally recognized as safe as an anti-caking agent in table salt up to 2% (21 CFR 182.2437). -Generally approved for use as a pigment or colorant in the manufacture of articles which come into contact with food, under the following citations: 21 CFR 174.5(d), 175.105, 175.125, 175.300(b)(3)(xivi), 175.320, 175.380,175.170(b)(2), 176.180(b)(2), 176.180(b)(1), 176.200, 177.1210, 177.1350, 177.1460, 177.2600(c)(1), 182.70,182.90.

-Generally approved for use in olefin polymers used in the manufacture of articles which come into contact with foods under 21 CFR 177.1520.

### TALC (14807-96-6)

Listed on IARC (International Agency for Research on Cancer

### Quartz (fine fraction) (14808-96-6)

Listed on IARC (International Agency for Research on Cancer

15.4 Other regulations based on domestic or foreign laws: The following inventories have been investigated as to the publicity available portion of the lists.

Component	CAS#	TSCA	DSL\NDSL	EINECS (EU)	AICS	KECI	CSNN
Country		USA	Canada	Europe	Aust.	Korea	Taiwan
Talc	14807-96-6	Yes	Yes (DSL)	Yes	Yes	Yes	Yes
Quartz (fine fraction)	14808-60-7	Yes	Yes	Yes	Yes	Yes	Yes

Component	CAS#	ENCS/ISH L	IECSC	PICCS	Swiss ID No.	NZIoC
Country		Japan	China	Philippines	Switzerland	New Zealand
Talc	14807-96-6	Yes	Yes	Yes	Yes	Yes
Quartz (fine fraction)	14808-60-7	Yes	Yes	Yes	Yes	Yes

Chemical Safety Assessment- REACH: Exempted from REACH registration in accordance with Annex V.7

# 15.5 Other Pertinent Classifications/Regulations:

Clean Air Act: Ozone depleting chemicals (ODC): None

CONEG Approved Packaging: Yes

Page 7 of 8 Revision: 20(09/20/2025)



# **SECTION 16 - OTHER INFORMATION**

# 16.1 References and Sources:

Data Sources: US OSHA HazCom (GHS) May 25, 2012. NFPA (National Fire Protection Association) Ratings:

Health Hazard:	1	Exposure could cause irritation but only minor residual injury even if no treatment is given
Fire Hazard	0	Materials will not burn
Reactivity	0	Normally stable, even under fire exposure conditions, and are not reactive with water

# LIMIC III Detinger

niviis iii Kalings.			
Health Hazard:	1	Slight	Irritation or minor reversible injury possible. Chronic Hazard- Chronic (long-term)
			effects may result from repeated overexposure
Flammability	0	Minimal	Materials will not burn
Physical	Е	Minimal	Materials are normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive.
-	-		
Personal	E		Safety glasses, gloves, dust respirator
Protection			

#### Acronyms:

EPA = Environmental Protection Agency

TSCA = Toxic Substance Control Act

ACGIH = American Conference of Governmental Industrial Hygienists

IARC = International Agency for Research on Cancer

NIOSH = National Institute for Occupational Safety and Health

NTP = National Toxicology Program

OSHA = Occupational Safety and Health Administration

DOT = Department of Transportation

RCRA = Resource Conservation and Recovery Act

#### Other Information:

Disclaimer: CIMBAR Performance Minerals (CPM) is not responsible for the use of information, product, method, or apparatus herein presented ("Information"), and you must make your own determination as to its suitability and completeness for your own use, for the protection of the environment, and for health and safety purposes. You assume the entire risk of relying on this information. In no event shall CPM be responsible for damages of any nature whatsoever resulting from the use of or reliance upon this information. By providing this information, CPM neither can nor intends to control the method or manner by which you use, handle, store, or transport CPM products. Nothing herein shall be construed as a recommendation or license to use any Information that conflicts with any patent, trademark or copyright. Safety Data Sheets providing safety precautions that should be observed in handling and storing CPM products are available upon request. You should obtain and review the available material safety information before handling any of these products.

CPM MAKES NO PRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE REGARDING THIS INFORMATION, AND NOTHING HEREIN WAIVES ANY CONDITIONS OF SALE.

This information could include technical inaccuracies or typographical errors. Changes are periodically added to the information herein; these changes will be incorporated in revisions of the information.

CPM may make improvements and/or changes in the product(s) described in this information at any given time.

SDS-TALC Page 8 of 8 Revision: 20(09/20/2025)