

HYBASE® GF-400

Version: 1.6 Revision Date: 09/04/2018 Print Date: 03/12/2019 SECTION 1. PRODUCT AND COMPANY IDENTIFICATION Product name: HYBASE® GF-400 Product Use Description: Raw material for industry Synonyms: calcium sulfonate detergent additive LANXESS Solutions US Inc. Company: 2 Armstrong Road Shelton, Ct 06484 United States of America (USA) Telephone: (US) +1 866-430-2775 Emergency telephone CHEMTREC: (24 hours) 800-424-9300 number: : US: 800-292-5898 (Technical inquiries) For additional emergency telephone numbers see section 16 of the Safety Data Sheet. Prepared by Product Safety Department (US) +1 866-430-2775 MSDSRequest@lanxess.com Recommended use of the chemical and restrictions on use Recommended use Raw material for industry : Restrictions on use For industrial use only. 1

SECTION 2. HAZARDS IDENTIFICATION

Form	viscous liquid
Colour	brown
Odour	mild hydrocarbon-like

GHS Classification

Eye irritation

: Category 2A

GHS label elements



HYBASE® GF-400

ion: 1.6	Revision Date: 09/04/2018	Print Date: 03/12/201
Signal word	: Warning	
Hazard pictograms		
Hazard statements	: H319 Causes serious eye irrita	tion.
Other hazards	None	
Precautionary statements	 Prevention: P264 Wash skin thoroughly after handling. P280 Wear eye protection/ face protection. Response: P305 + P351 + P338 IF IN EYES: Rinse cautiously with wat for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 If eye irritation persists: Get medical advice/ attention. 	
Carcinogenicity:		
IARC	No component of this product pres equal to 0.1% is identified as proba human carcinogen by IARC.	
OSHA	No component of this product pres equal to 0.1% is on OSHA's list of	
NTP	No component of this product pres equal to 0.1% is identified as a kno by NTP.	sent at levels greater than or

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical name	CAS-No.	Concentration (%)
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	>= 30 - < 50 %
calcium carbonate	471-34-1	>= 30 - < 50 %
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts	68584-23-6	>= 10 - < 20 %
Sulfonic acids, petroleum, calcium salts	61789-86-4	>= 1 - < 5 %
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts	70024-69-0	>= 1 - < 5 %
calcium dihydroxide	1305-62-0	>= 2.5 - < 3 %

SAFETY DATA SHEET

HYBASE® GF-400

Version: 1.6	Revision Date: 09/04/2018	Print Date: 03/12/2019
SECTION 4. FIRST AID MEASU	RES	
If inhaled	 Remove to fresh air. If breathing is difficult, give oxyge If symptoms persist, call a physici 	
In case of skin contact	 Wash off with warm water and so Cool skin rapidly with cold water a material. If skin irritation persists, call a phy Wash contaminated clothing befo 	after contact with molten ysician.
In case of eye contact	 Rinse immediately with plenty of v for at least 10 minutes. If eye irritation persists, consult a 	
If swallowed	 Do NOT induce vomiting. Prevent vomiting if possible. Rinse mouth with water. Obtain medical attention. Never give anything by mouth to an unconscious person. 	
Most important symptoms and effects, both acute and	: irritant effects	
delayed Notes to physician	: For specialist advice physicians s Information Service.	should contact the Poisons

SECTION 5. FIREFIGHTING MEASURES

SAP 6.0 SDS 2012-2 NA GHS	3 / 13	SDS Number: 00000001255
Specific extinguishing	: Cool containers/tanks with water sp	ray.
Specific hazards during firefighting	: Do not use a solid water stream as fire. Burning produces noxious and toxic	
Unsuitable extinguishing media	: Water spray jet	
Suitable extinguishing media	: (on small fires) Carbon dioxide (CO2) Dry chemical Dry sand Extinguishing media - large fires Foam Water mist	



HYBASE® GF-400

Version: 1.6	Revision Date: 09/04/2018	Print Date: 03/12/2019
methods	Prevent fire extinguishing water f water or the ground water system	-
Special protective equipment for firefighters	: In the event of fire, wear self-con Use personal protective equipme	• • • •
SECTION 6. ACCIDENTAL RELEA	ASE MEASURES	
Personal precautions, protective equipment and emergency procedures	: Wear suitable protective equipmer Ensure adequate ventilation.	ent.
Environmental precautions	: Should not be released into the e Do not flush into surface water o	
Methods and materials for containment and cleaning up	: Clean-up methods - large spillag should be collected mechanically disposal. Clean-up methods - sr inert absorbent material (e.g. sar universal binder, sawdust). Pick labelled containers.	y (remove by pumping) for mall spillage Soak up with nd, silica gel, acid binder,

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 Handle and open container with care. Ensure all equipment is electrically grounded before beginning transfer operations. Protect from contamination. Do not use in areas without adequate ventilation. Wear suitable protective equipment. Keep container closed when not in use.
Conditions for safe storage	: Keep containers tightly closed in a dry, cool and well- ventilated place.
Materials to avoid	: Oxidizing agents, Strong acids and strong bases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
SAP 6.0 SDS 2012-2 NA GHS	4 /	13	SDS Nu	mber: 000000001255



HYBASE® GF-400

Version: 1.6

Revision Date: 09/04/2018

Print Date: 03/12/2019

Distillates (petroleum), solvent- refined heavy paraffinic	64741-88-4	TWA	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		TWA (Mist)	5 mg/m3	OSHA P0
		PEL (particulate)	5 mg/m3	CAL PEL
calcium carbonate	471-34-1	PEL (Total dust)	10 mg/m3	CAL PEL
		PEL (respirable dust fraction)	5 mg/m3	CAL PEL
		TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
calcium dihydroxide	1305-62-0	TWA	5 mg/m3	ACGIH
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA	5 mg/m3	OSHA P0
		TWA	5 mg/m3	NIOSH REL
		PEL	5 mg/m3	CAL PEL

Engineering measures	 Effective exhaust ventilation system Ensure that extracted air cannot be through the ventilation system. Ensure that eyewash stations and so the workstation location. 	e returned to the workplace
Personal protective equipr	nent	
Respiratory protection	 No personal respiratory protective or required. When workers are facing concentration limit they must use appropriate certor Respirator with combination filter for 141) 	ations above the exposure tified respirators.
Hand protection Remarks	: Impervious gloves	
Eye protection	: Tightly fitting safety goggles	
Skin and body protection	: Impervious clothing	
SAP 6.0 SDS 2012-2 NA GHS	5 / 13	SDS Number: 00000001255



HYBASE® GF-400

Version: 1.6	Revision Date: 09/04/2018	Print Date: 03/12/2019
Hygiene measures	 Handle in accordance with good practice. Wear suitable gloves and eye/fac Avoid contact with skin, eyes and Do not eat, drink or smoke when Wash thoroughly after handling. Remove and wash contaminated 	ce protection. d clothing. using this product.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: viscous liquid	
Color	: brown	
Odor	: mild hydrocarbon-like	
Odour Threshold	: No data available	
рН	: No data available	
	: Not oppliachte	
	Not applicable	
Boiling point/boiling range	: No data available	
Evaporation rate	: No data available	
Flash point	: 193 °C Method: Cleveland open cup	
Upper explosion limit	: No data available	
Lower explosion limit	: No data available	
Vapour pressure	: < 0.1 hPa (20 °C)	
Relative vapour density	: No data available	
Relative density	: >1 (16 °C)	
Density	: > 1 g/cm3 (25 °C)	
Solubility(ies)		
Water solubility	: negligible	
Solubility in other solvents	: partly soluble Solvent: Hydrocarbons	
Partition coefficient: n- octanol/water	: No data available	
Auto-ignition temperature	: No data available	
SAP 6.0 SDS 2012-2 NA GHS	6 / 13	SDS Number: 00000001255

SAFETY DATA SHEET

HYBASE® GF-400

/ersion: 1.6	Revision Date: 09/04/2018	Print Date: 03/12/2019
Viscosity		
Viscosity, dynamic	: 50 mPa.s (100 °C) Method: ASTM D 445	
Viscosity, kinematic	: > 30 mm2/s (40 °C)	
Molecular weight	: No data available	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Hazardous polymerisation does not occur.
Conditions to avoid	: Extremes of temperature and direct sunlight. Contamination
Incompatible materials	: Oxidizing agents Strong acids and strong bases
Hazardous decomposition products	: Carbon oxides Nitrogen oxides (NOx) Sulphur oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity		
Product:		
Acute oral toxicity	: LD50 (Rat): > 20,000 mg/kg Remarks: Information given is based similar substances.	on data obtained from
Acute dermal toxicity	: Acute toxicity estimate: > 5,000 mg/k Method: Calculation method	g
Components: calcium carbonate: Acute oral toxicity	: LD50 (Rat): 6,450 mg/kg	
SAP 6.0 SDS 2012-2 NA GHS	7 / 13	SDS Number: 00000001255



HYBASE® GF-400

sion: 1.6	Revision Date: 09/04/2018	Print Date: 03/12/201
Sulfonic acids, petroleum	, calcium salts:	
Acute oral toxicity	: LD50 (Rat, male and female): >	
	Method: OECD Test Guideline 4	01
	GLP: yes	
Acute dermal toxicity	: LD50 (Rabbit, male and female):	> 1.000 mg/kg
Acute definal toxicity	Method: OECD Test Guideline 4	
	GLP: yes	
calcium dihydroxide:		
Acute oral toxicity	: LD50 (Rat): 7,340 mg/kg	
Skin corrosion/irritation		
Components:		
calcium carbonate:		
Species: Rabbit		
Result: No skin irritation		
calcium dihydroxide:		
Result: Irritating to skin.		
.		
Serious eye damage/eye i	rritation	
Components:		
calcium carbonate:		
Species: Rabbit		
Result: No eye irritation		
calcium dihydroxide: Species: Rabbit		
Result: Risk of serious dam	age to eves	
Method: Draize Test		
Respiratory or skin sensit	isation	
Product:		
Result: Does not cause skir	i sensilisation.	
Components:		
	0-16-alkyl derivs., calcium salts:	
	nce of low to moderate skin sensitisation	rate in humans
Result: Probability or evider		
Result: Probability or evider		
Sulfonic acids, petroleum		
Sulfonic acids, petroleum	, calcium salts: nce of low to moderate skin sensitisatior	n rate in humans



HYBASE® GF-400

nsitisation on laboratory animals. No component of this product pres	
equal to 0.1% is identified as proba human carcinogen by IARC.	
No component of this product pres equal to 0.1% is on OSHA's list of	
No component of this product presequal to 0.1% is identified as a know by NTP.	
: Species: Rat Application Route: Oral	
: No toxicity to reproduction No effects on or via lactation	
atory irritation.	
tion	
on the product itself.	
	equal to 0.1% is on OSHA's list of No component of this product presequal to 0.1% is identified as a know by NTP.

SAFETY DATA SHEET

	HYBASE® GF-400	
rsion: 1.6	Revision Date: 09/04/2018	Print Date: 03/12/201
Ecotoxicity		
Product:		
Toxicity to fish	: Remarks: No data available	
Components:		
Sulfonic acids, petroleum, ca	alcium salts:	
Toxicity to fish	 LC50 (Cyprinodon variegatus (10,000 mg/l Exposure time: 96 h Test Type: static test Method: OECD Test Guideline GLP: yes 	
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water Exposure time: 48 h Test Type: static test Method: OECD Test Guideline GLP: yes	
Toxicity to algae	: EbC50 (Green algae (Scenede Exposure time: 72 h Test Type: static test Analytical monitoring: no Method: OECD Test Guideline GLP: yes	esmus subspicatus)): > 100 mg/l 201
	ErC50 (Green algae (Scenede Exposure time: Test Type: static test Analytical monitoring: no Method: OECD Test Guideline GLP: yes	smus subspicatus)): > 100 mg/l 201
calcium dihydroxide:		
Toxicity to fish	: LC50 (Gambusia affinis (Mosq Exposure time: 96 h Test Type: static test	uito fish)): 160 mg/l
Ecotoxicology Assessment		
Acute aquatic toxicity	: Harmful to aquatic life.	
Persistence and degradabilit	ÿ	
Product:		
Biodegradability	: Result: No data available	

SAFETY DATA SHEET

HYBASE® GF-400

rsion: 1.6	Revision Date: 09/04/2018	Print Date: 03/12/2019
Components:		
Sulfonic acids, petroleu	m, calcium salts:	
Biodegradability	: aerobic Inoculum: activated sludge Result: Not readily biodegradable. Biodegradation: 8.6 % Exposure time: 28 d GLP: yes	
Bioaccumulative potent	ial	
Product:		
Bioaccumulation	: Remarks: No data available	
Mobility in soil		
Product:		
Mobility	: Remarks: No data available	
Other adverse effects		
Product: Results of PBT and vPvB assessment	: No data available	
Additional ecological information	: The product itself has not been tes Avoid release to the environment.	sted.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	:	In accordance with local and national regulations.
		Dispose of wastes in an approved waste disposal facility.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

SAP 6.0 SDS 2012-2 NA GHS

SDS Number: 00000001255



HYBASE® GF-400

Version: 1.6

Revision Date: 09/04/2018

Print Date: 03/12/2019

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

Not classified as dangerous in the meaning of transport regulations.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
naphthalene	91-20-3	100	*
xylene	1330-20-7	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA304 Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	:	Serious eye damage or eye irritation
SARA 302	:	This material does not contain any components with a section 302 EHS TPQ.
SARA 313	:	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

California Prop. 65

WARNING: This product can expose you to chemicals including naphthalene, ethylbenzene, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.



HYBASE® GF-400

Version: 1.6	Revision Date: 09/04/2018	Print Date: 03/12/2019

Please note that Section 3 of this document lists only the hazardous components required by the specific country or region hazard communication regulations. The chemical identifiers listed in Section 3 are used globally for hazard communication purposes and may not reflect those used for chemical inventory coverage in a particular country or region. The chemical inventory information given in Section 15 of this document applies to the product as a whole and should be used when evaluating inventory compliance.

e reported in the following inventories:
mponents of this product are on the Canadian DSL
e inventory, or in compliance with the inventory
e inventory, or in compliance with the inventory
e inventory, or in compliance with the inventory
e inventory, or in compliance with the inventory
e inventory, or in compliance with the inventory
e inventory, or in compliance with the inventory
e inventory, or in compliance with the inventory
SCA Inventory
)))))

SECTION 16. OTHER INFORMATION

Further information

Other Emergency Phone Number

Latin America:	Brazil	+55 113 711 9144
	All other countries	+44 (0) 1235 239 670
<u>Mexico:</u>		+52 555 004 8763

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.