



TECHNICAL DATA SHEET

COPRO® SP-490

Description	A multi-functional acrylic emulsion polymer	
Application	Designed as polymer for use in elastomeric roof coatings and other specialty applications.	
Features	 Excellent flexibility Excellent adhesion to a variety of substrates High water resistance Excellent clarity and UV stability Easy to formulate to meet specific performance needs 	
Properties	Negyaletila Content 0/	55.0 – 57.0
	Nonvolatile Content, %	6.5 – 7.5
	Viscosity, cps	500 max
	(Brookfield, RV, #2/20rpm/25C°/77°F)	ood max
	Wt/gal	8.5 - 8.7
	Glass transition temperature (Tg), °C	-39
Storage	Protect from freezing. Ideal storage temperature 72°F. Stability at 72°F is >180 days.	
Packaging Forms	Available in bulk, totes or drums.	
Important Safety Information	Before using this or any other chemical product, be sure to read and understand the information on the Safety Data Sheet and Product Labels. Remain aware of potential hazards and follow all precautiona measures, handling instructions, and disposal considerations outlined the SDS and label.	
	Rev 12/15	

For help in a Chemical Emergency, call CHEMTREC at 1-800-424-9300

IMPORTANT: Information, specifications, procedures and recommendations provided ("information") are based on our experience and we believe this to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that use of the product will avoid losses or damages or give desired results. It is purchaser's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

NOTE TO USER: by ordering/receiving product you accept the H.B. Fuller General Terms and Conditions of Sale applicable in the region. Please request a copy if you have not received these. These Terms and Conditions contain disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose) and limits of liability. All other terms are rejected. In any event, the total aggregate liability of H.B. Fuller for any claim or series of related claims however arising, in contract, tort (including negligence), breach of statutory duty, misrepresentation, strict liability or otherwise, is limited to replacement of affected products or refund of the purchase price for affected products. H.B. Fuller shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill or any indirect or consequential losses arising out of or in connection with product supply.



H.B. Fuller North America inquiry@hbfuller.com
Contact us for details