



WIRE & CABLE

ROYALE BLACK[®] PC503

PRODUCT PROFILE

PC503 exhibits good UV protection in various plastic applications such as cable jacketing, telecom jacketing and mulch film.

PC503 contains very low sulphur and low ash which improves cable life. It provides good surface smoothness of jacketing compound.

Very low sieve residue and ash content of PC503 prevent washout of any ionisable material which results initiation of electrical degradation site.

TYPICAL VALUE

NSA m ² /g	STSA m ² /g	OAN cc/100g	Tint Strength % ITRB	Sieve Residue 325M, ppm	Heating Loss (As Shipped) %
124	112	117	114	12	0.5

APPLICATION FIELD

TYPICAL APPLICATION	RECOMMENDED DOSAGE
Thermoplastic	Upto 35%

- Recommended dosage can vary depending upon end use and modification of other ingredients
- Packaging - 25kg paper bag or 500/1000kg bulk bag

PCBL Limited

Registered Office: 31 Netaji Subhas Road, Kolkata - 700 001, WB, India
Corporate Office: RPSG House, 4th Floor, 2/4 Judges Court Road, Kolkata - 700 027, WB, India
P: +91 33 6625 1443 | **F:** +91 33 2248 0140/2243 6681 | **W:** www.pcbltd.com | **E:** pcbl.specialtyblack@rpsg.in

Revision No. - 03
Issue - Mar. 2023

