

SAFETY DATA SHEET

1. IDENTIFICATION

Product Name: EBECRYL® 350 radiation curing resins
Synonyms: None
Product Description: Silicone acrylate derivative
Molecular Formula: Mixture
Molecular Weight: Mixture
Intended/Recommended Use: Radiation curable coating ingredient, Coatings & Inks

Allnex USA Inc., 9005 Westside Parkway, Alpharetta, Georgia 30009, USA

For Product and all Non-Emergency Information call your local Allnex contact point or contact us at <http://www.allnex.com/contact>

EMERGENCY PHONE (24 hours/day) - For emergency only involving spill, leak, fire, exposure or accident call:
+1-866-928-0789 (toll free) or +1-215-207-0061 (Carechem 24 - Allnex29003-NCEC)
See Section 16 for Emergency phone numbers for other regions.

Trademarks indicated with ® , TM or * as well as the allnex name and logo are registered, unregistered or pending trademarks of Allnex Netherlands BV or its directly or indirectly affiliated allnex Group companies.

2. HAZARDS IDENTIFICATION

GHS Classification

Serious Eye Damage / Eye Irritation Hazard Category 2A
Aquatic Environment Acute Hazard Category 3

LABEL ELEMENTS



Signal Word

WARNING

Hazard Statements

Causes serious eye irritation
Harmful to aquatic life

Precautionary Statements

Wash face, hands and any exposed skin thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.
Avoid release to the environment.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Dispose of contents/container in accordance with local and national regulations.

Hazards Not Otherwise Classified (HNOC), Other Hazards

Contact with skin may cause a cross-allergic reaction in persons already sensitized to acrylates.

3. COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS

| Component / CAS No. | % | GHS Classification |
|-----------------------------|----------|---|
| Acrylic acid 79-10-7 | < 0.3 | Flam. Liq. 3 (H226) Acute Tox. 4 (H302) Acute Tox. 4 (H312) Acute Tox. 4 (H332) STOT Single 3 (H335) Skin Corr. 1A (H314) Eye Dam. 1 (H318) Aquatic Acute 1 (H400) Aquatic Chronic 2 (H411) |
| 4-Methoxyphenol 150-76-5 | < 0.25 | Acute Tox. 4 (H302) Skin Irrit. 3 (H316) Eye Irrit. 2A (H319) Skin Sens. 1B (H317) Aquatic Acute 2 (H401) Aquatic Chronic 3 (H412) |
| Acrylated resin - | 99 - 100 | Skin Irrit. 3 (H316) Eye Irrit. 2A (H319) |

The specific chemical identity and/or exact percentage of composition for one or more ingredients has been withheld as a trade secret.

Additional GHS classification or other information may be included in this section but has not been adopted by OSHA. See Section 16 for full text of H phrases.

4. FIRST AID MEASURES

First-aid Measures**Inhalation:**

Remove to fresh air. If breathing is difficult, give oxygen. Obtain medical advice if there are persistent symptoms.

Skin Contact:

Wash immediately with plenty of water and soap.

Eye Contact:

Rinse immediately with plenty of water for at least 15 minutes. Obtain medical advice if there are persistent symptoms.

Ingestion:

If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

Most Important Symptoms and Effects, Acute and Delayed

None known.

Immediate Medical Attention and Special Treatment

Not applicable.

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Notes To Physician:

No specific measures have been identified.

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media:**

Use water spray or fog, carbon dioxide or dry chemical.

Unsuitable Extinguishing Media:

full water jet, high pressure water jet.

Protective Equipment:

Firefighters, and others exposed, wear self-contained breathing apparatus. Wear full firefighting protective clothing. See SDS Section 8 (Exposure Controls/Personal Protection).

Special Hazards:

Keep containers cool by spraying with water if exposed to fire.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions:**

Where exposure level is not known, wear approved, positive pressure, self-contained respirator. Where exposure level is known, wear approved respirator suitable for level of exposure. In addition to the protective clothing/equipment in Section 8 (Exposure Controls/Personal Protection), wear impermeable boots.

Methods For Cleaning Up:

Cover spills with some inert absorbent material; sweep up and place in a waste disposal container. Flush spill area with water.

Environmental Precautions:

Avoid release to the environment.

References to other sections:

See Sections 7, 8 and 13 for additional information.

7. HANDLING AND STORAGE**HANDLING**

Precautions: Wash hands thoroughly after handling. Wear eye/face protection. Avoid release to the environment.

Special Handling Statements: Provide good ventilation of working area (local exhaust ventilation if necessary). Avoid excessive heat, contamination or exposure to direct sunlight to prevent polymerization.

STORAGE

Store in a cool, dry, well ventilated place and keep container tightly closed. Keep away from heat sources and direct sunlight.

Storage Temperature: Store at 15 - 40 °C 59 - 104 °F

Reason: Quality.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Measures:

Where this material is not used in a closed system, good enclosure and local exhaust ventilation should be provided to control exposure.

Respiratory Protection:

For operations where inhalation exposure can occur use an approved respirator. Recommendations are listed below. Other protective respiratory equipment may be used based on user's own risk assessment. Recommended respirators include those certified by NIOSH.

Recommended:

Full Face Mask with organic vapor cartridge, Type A filter (BP >65°C)

Eye Protection:

Wear eye/face protection such as chemical splash proof goggles or face shield. Eyewash equipment and safety shower should be provided in areas of potential exposure.

Skin Protection:

Avoid skin contact. Wear impermeable gloves and suitable protective clothing.

Hand Protection:

Wear protective gloves. Recommendations are listed below. Other protective materials may be used based on user's own risk assessment. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred. Replace gloves immediately when torn or any change in appearance (dimension, color, flexibility etc.) is noticed.

Gloves for repeated or prolonged exposure - non exhaustive list:

Nitrile rubber (NBR), thickness: > 0.56 mm, break through time: up to 480 min

Gloves for short term exposure/splash protection - non exhaustive list:

Nitrile rubber (NBR), thickness: 0.1 mm, break through time: up to 30 min

The chemical resistance depends on the type of product and amount of product on the glove. Therefore gloves need to be changed when in contact with chemicals.

Not suitable gloves - non exhaustive list:

Latex gloves

Due to many conditions (e.g. temperature, abrasion) the practical usage of a chemical protective glove in practice may be much shorter than the permeation time determined through testing. Use PE gloves as under gloves for difficult situations like for instance: high exposure, unknown composition or unknown properties of the chemicals.

Additional Advice:

Food, beverages, and tobacco products should not be carried, stored, or consumed where this material is in use. Before eating, drinking, or smoking, wash face and hands thoroughly with soap and water.

Exposure Limit(s)

79-10-7 Acrylic acid

OSHA (PEL): Not established

ACGIH (TLV): (skin)

2 ppm (TWA)

Other Value: 1 ppm skin (Allnex)

150-76-5 4-Methoxyphenol

| | |
|--------------|---------------------------|
| OSHA (PEL): | Not established |
| ACGIH (TLV): | 5 mg/m ³ (TWA) |
| Other Value: | Not established |

Biological Exposure Limit(s)

No values have been established.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|----------------------------------|
| Color: | clear pale yellow |
| Appearance: | clear liquid |
| Odor: | ester-like |
| Boiling Point: | > 100 °C 212 °F |
| Melting Point: | Not available |
| Vapor Pressure: | < 1.33 hPa @ 20 °C |
| Specific Gravity/Density: | 1.05 g/cm ³ |
| Vapor Density: | Not available |
| Percent Volatile (% by wt.): | < 0.3 |
| pH: | Not available |
| Saturation In Air (% By Vol.): | Not available |
| Evaporation Rate: | Not available |
| Solubility In Water: | Insoluble |
| Volatile Organic Content: | Not available |
| Flash Point: | 265 °C 509 °F Cleveland Open Cup |
| Flammable Limits (% By Vol): | Not applicable |
| Autoignition Temperature: | Not available |
| Decomposition Temperature: | Not available |
| Partition coefficient n-octanol/water (log value): | Not available |
| Odor Threshold: | Not available |
| Viscosity (Kinematic): | Not available |
| Viscosity (Dynamic): | 200 - 500 mPa.s @ 25 °C |
| Flammability: | Normal combustion |
| Oxidizing Properties: | Not available |

Other safety characteristics

Not applicable

10. STABILITY AND REACTIVITY

Reactivity: No information available

Stability: Stable.

Conditions To Avoid: Avoid direct exposure to sunlight. Avoid temperatures higher than 60°C. Avoid friction with temperature increase as result. Avoid exposure to strong UV sources. Loss of dissolved air. Loss of polymerization inhibitor. Avoid direct contact with heat sources.

Polymerization: May occur

Conditions To Avoid: Uncontrolled polymerization may cause rapid evolution of heat and increase in pressure that could result in violent rupture of sealed storage vessels or containers

Hazardous polymerization can occur when exposed to direct sunlight. Hazardous exothermic polymerization can occur when heated.

Materials To Avoid:

Polymerization initiators including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron, rust, and strong bases. Hazardous polymerization may occur. Uncontrolled polymerization may cause rapid evolution of heat and increase in pressure that could result in violent rupture of sealed storage vessels or containers.

Hazardous Decomposition Products:

oxides of carbon
hydrocarbons
Silicium oxides

11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Skin, Eyes, Oral.

Acute toxicity - oral: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

Acute toxicity - dermal: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

Acute toxicity - inhalation: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

Skin corrosion / irritation: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

Serious eye damage / eye irritation: Causes serious eye irritation

Respiratory sensitization: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

Skin sensitization: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

Carcinogenicity: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

Germ cell mutagenicity: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

Reproductive toxicity: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

Specific target organ toxicity (STOT) - single exposure: Not Classified. - Based on available data and/or professional judgment, the classification criteria are not met.

Specific target organ toxicity (STOT) - repeated exposure: Not Classified. - Based on available data and/or professional judgment, the classification criteria are not met.

Aspiration hazard: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

PRODUCT TOXICITY INFORMATION

ACUTE TOXICITY DATA

| | | | | |
|------------|--------|------------|--------|---------|
| oral | rat | Acute LD50 | > 2000 | mg/kg |
| dermal | rabbit | Acute LD50 | > 2000 | mg/kg |
| Inhalation | rat | Acute LC50 | 4 hr | No data |

LOCAL EFFECTS ON SKIN AND EYE

| | | | |
|------------------|------|--------|------------------------|
| Acute Irritation | Skin | rabbit | Not irritating |
| Acute Irritation | eye | rabbit | Irritating (estimated) |

ALLERGIC SENSITIZATION

| | | |
|---------------|-------------|---------|
| Sensitization | Skin | No data |
| Sensitization | respiratory | No data |

SUBACUTE/SUBCHRONIC TOXICITY

| | | |
|---------------|-----|---------|
| oral (gavage) | rat | No data |
| dermal | rat | No data |

GENOTOXICITY**Assays for Gene Mutations**

| | |
|-----------------------|---------|
| Ames Salmonella Assay | No data |
|-----------------------|---------|

OTHER INFORMATION

The product toxicity information above has been estimated.

Contact with skin may cause a cross-allergic reaction in persons already sensitized to acrylates.

Prolonged or repeated contact with skin or mucous membrane may result in irritation symptoms such as redness, blistering, dermatitis, etc.

The inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.

HAZARDOUS INGREDIENT TOXICITY DATA

Acrylic acid has acute oral (rat) LD50, acute dermal (rabbit) LD50, and acute inhalation (rat, 4-hr, vapor) LC50 values of 617-1405 mg/kg, >2000 mg/kg, and >1730 ppm (>5.1 mg/L), respectively. Direct contact may cause severe eye irritation with corneal injury which may result in permanent impairment of vision and even blindness. Chemical burns may occur. Vapors may also cause severe eye irritation. Skin contact may cause severe skin burns. Symptoms may include pain, severe local redness, swelling, blistering and tissue damage. Inhalation overexposure may cause severe irritation of the respiratory tract. Repeated overexposures may have effects on the kidney. Acrylic acid did not cause cancer when given to rats in their drinking water throughout their lifetime. No skin tumors occurred in mice receiving repeated skin applications of acrylic acid at nonirritating doses. A slight, not statistically significant increase in skin tumors reported in another study is difficult to interpret due to the low incidence and conflicting information regarding dose. This substance has been toxic to the fetus in laboratory animals at doses toxic to the mother but has not been found to cause birth defects in laboratory animals. In laboratory animal studies with acrylic acid, effects on reproduction have been seen only at doses that produced significant toxicity to the parent animals. The results of in vitro genetic toxicity studies are predominantly negative. Animal genetic toxicity studies are negative (not mutagenic).

4-Methoxyphenol has an oral LD50 of 1630 mg/Kg (rat), and a dermal LD50 of > 2000 mg/Kg (rat). Suspect skin sensitizer (guinea pig). 4-Methoxyphenol is a moderate to severe eye irritant and a slight skin irritant. Ingestion causes gastrointestinal irritation with nausea and vomiting and possibly ulceration. Overexposure (ingestion/inhalation) can cause methemoglobinemia with cyanosis, as well as central nervous system (CNS) depression, with symptoms ranging from headache, and confusion, to coma, and respiratory failure. 4-Methoxyphenol may be absorbed through skin, causing symptoms similar to ingestion/inhalation exposure routes. In vitro testing hasn't revealed genotoxic effects. This was confirmed by an in vivo clastogenicity study. No increase in tumour incidence was observed in several carcinogenicity assays. In a weight of evidence approach based on 3 reliable studies, it was concluded that 4-Methoxyphenol is not a teratogen when maternal animals do not suffer from severe toxicity. Reproductive performance was not affected by 4-Methoxyphenol in a extended one generation reproductive toxicity study in rats.

Acrylated resin - The toxicological properties of this material have not been fully evaluated. Contact may cause moderate eye irritation. Skin irritation (rabbit) - slightly irritating to skin.



WARNING: Reproductive Harm – www.P65Warnings.ca.gov

12. ECOLOGICAL INFORMATION

TOXICITY, PERSISTENCE AND DEGRADABILITY, BIOACCUMULATIVE POTENTIAL, MOBILITY IN SOIL, OTHER ADVERSE EFFECTS

Overall Environmental Toxicity: Harmful to aquatic life.

The ecological assessment for this material is based on an evaluation of its components.

RESULTS OF PBT AND vPvB ASSESSMENT

Not determined

HAZARDOUS INGREDIENT TOXICITY DATA

| Component / CAS No. | Toxicity to Fish |
|----------------------------|--|
| Acrylic acid (79-10-7) | LC50 = 27 mg/L - Salmo gairdneri (96h) |
| 4-Methoxyphenol (150-76-5) | LC50 = 28.5 mg/L - Oncorhynchus mykiss (96hrs) |
| Acrylated resin (-) | Not available |

| Component / CAS No. | Toxicity to Water Flea |
|----------------------------|---|
| Acrylic acid (79-10-7) | EC50 = 47 mg/L - Daphnia magna (48h) EC50 = 95 mg/L - Daphnia magna (48h) NOEC = 12-19 mg/L - Daphnia magna (21d) |
| 4-Methoxyphenol (150-76-5) | EC50 = 3 mg/L - Daphnia magna (48hrs) NOEC = 0.68 mg/L - Daphnia magna (21d) |
| Acrylated resin (-) | Not available |

| Component / CAS No. | Toxicity to Algae |
|----------------------------|--|
| Acrylic acid (79-10-7) | EC50 = 0.13 mg/L - Scenedesmus subspicatus (72h) EC10 = 0.03 mg/L - Scenedesmus subspicatus (72h) |
| 4-Methoxyphenol (150-76-5) | EC50 = 54.7 mg/L - Pseudokirchnerella subcapitata (72hrs) NOEC = 2.96 mg/L - Pseudokirchnerella subcapitata (72hrs) |
| Acrylated resin (-) | Not available |

| Component / CAS No. | Partition coefficient |
|----------------------------|-----------------------|
| Acrylic acid (79-10-7) | 0.46 |
| 4-Methoxyphenol (150-76-5) | log Kow = 1.3 |
| Acrylated resin (-) | Not available |

13. DISPOSAL CONSIDERATIONS

The information on RCRA waste classification and disposal methodology provided below applies only to the product, as supplied. If the material has been altered or contaminated, or it has exceeded its recommended shelf life, the guidance may be inapplicable. Hazardous waste classification under federal regulations (40 CFR Part 261 et seq) is dependent upon whether a material is a RCRA "listed hazardous waste" or has any of the four RCRA "hazardous waste characteristics." Refer to 40 CFR Part 261.33 to determine if a given material to be disposed of is a RCRA "listed hazardous waste"; information contained in Section 15 of this SDS is not intended to indicate if the product is a

"listed hazardous waste." RCRA Hazardous Waste Characteristics: There are four characteristics defined in 40 CFR Section 261.21-61.24: Ignitability, Corrosivity, Reactivity, and Toxicity. To determine Ignitability, see Section 9 of this SDS (flash point). For Corrosivity, see Sections 9 and 14 (pH and DOT corrosivity). For Reactivity, see Section 10 (incompatible materials). For Toxicity, see Section 3 (composition). Federal regulations are subject to change. State and local requirements, which may differ from or be more stringent than the federal regulations, may also apply to the classification of the material if it is to be disposed. The Company encourages the recycle, recovery and reuse of materials, where permitted, as an alternate to disposal as a waste. The Company recommends that organic materials classified as RCRA hazardous wastes be disposed of by thermal treatment or incineration at EPA approved facilities. The Company has provided the foregoing for information only; the person generating the waste is responsible for determining the waste classification and disposal method.

14. TRANSPORT INFORMATION

This section provides basic shipping classification information. Refer to appropriate transportation regulations for specific requirements.

US DOT

Dangerous Goods? Not applicable/Not regulated

TRANSPORT CANADA

Dangerous Goods? Not applicable/Not regulated

ICAO / IATA

Dangerous Goods? Not applicable/Not regulated

IMO

Dangerous Goods? Not applicable/Not regulated

SPECIAL PRECAUTIONS FOR USER

Keep away from heat. Protect against external heat sources higher than +40°C/104°F.

15. REGULATORY INFORMATION

Inventory Information

United States (USA): All components of this product are designated as "Active" on the TSCA Inventory or are not required to be listed.

Canada: All components of this product are included on the Domestic Substances List (DSL) or are not required to be listed on the DSL.

European Economic Area (including EU): When purchased and shipped from an Allnex legal entity based in the EEA (EU or Norway), this product is compliant with the registration of the REACH Regulation (EC) No. 1907/2006 as all its components are either excluded, exempt and/or registered.

United Kingdom: When purchased from allnex UK this product is compliant with the UK-REACH Regulation as all its components are either notified, excluded, exempt and/or registered. If the material has been purchased by your legal entity based in GB from an allnex legal entity based in the EEA (EU or Norway) in 2019 or 2020, you can continue to import the material into GB as it is covered by allnex DUIN.

Australia: All components of this product are included in the Australian Inventory of Industrial Chemicals (AIIC)

or are not required to be listed on AIIIC.

New Zealand: This product is approved or exempt under the Hazardous Substances and New Organisms (HSNO) Act.

China: All components of this product are included on the Chinese inventory or are not required to be listed on the Chinese inventory.

Japan: All components of this product are included on the Japanese (ENCS) inventory or are not required to be listed on the Japanese inventory.

Korea: All components of this product are included on the Korean (ECL) inventory or are not required to be listed on the Korean inventory. When purchased from Allnex Korea or Chemart distributor this product is compliant with the ARECs (the Act on the Registration and Evaluation, etc. of Chemical Substances). All its components are either excluded, exempt, pre-notified and/or registered. When purchased from another allnex entity, please contact PSRA-KREACH@allnex.com to check the possibility to be covered by our Only Representative.

Philippines: One or more components of this product are NOT included on the Philippine (PICCS) inventory.

Taiwan: All components of this product are included in the Taiwan chemical substance inventory or are not required to be listed on the Taiwan chemical substance inventory (TCSI).

Switzerland: All components of this product are exempt from the new substance notification requirements for Switzerland (SR 813.11 art. 24-26).

Turkey: When purchased directly from Allnex by a Turkish legal entity, this product is compliant with the PRE-registration requirements of KKDIK as all its components are either pre-registered, excluded and/or exempt.

OTHER ENVIRONMENTAL INFORMATION

The following components of this product may be subject to reporting requirements pursuant to Section 313 of CERCLA (40 CFR 372), Section 12(b) of TSCA, or may be subject to release reporting requirements (40 CFR 307, 40 CFR 311, etc.) See Section 13 for information on waste classification and waste disposal of this product.

This product does not contain any components regulated under these sections of the EPA

PRODUCT HAZARD CATEGORY UNDER SECTIONS 311 AND 312 OF EPCRA

Physical Hazards

Not applicable

Health Hazards

Serious eye damage or eye irritation

16. OTHER INFORMATION

NFPA Hazard Rating (National Fire Protection Association)

Health: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

Fire: 1 - Materials that must be preheated before ignition can occur.

Instability: 1 - Materials that in themselves are normally stable, but that can become unstable at elevated temperatures and pressures.

Reasons for Issue: Revised Section 1

Date Prepared: 08/28/2024

Date of last significant revision: 03/06/2022

Component - Hazard Statements

Acrylic acid

H226 - Flammable liquid and vapor.
H302 - Harmful if swallowed.
H312 - Harmful in contact with skin.
H314 - Causes severe skin burns and eye damage.
H318 - Causes serious eye damage.
H332 - Harmful if inhaled.
H335 - May cause respiratory irritation.
H400 - Very toxic to aquatic life.
H411 - Toxic to aquatic life with long lasting effects.

4-Methoxyphenol

H302 - Harmful if swallowed.
H316 - Causes mild skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H401 - Toxic to aquatic life.
H412 - Harmful to aquatic life with long lasting effects.

Acrylated resin

H316 - Causes mild skin irritation.
H319 - Causes serious eye irritation.

Emergency phone numbers for other regions**Asia Pacific**

Australia: +61 1800 022 037 (Allnex Australia)
China (PRC): +86 532 8388 9090 (NRCC)
India: 000 800 100 7479 (toll free) or +65 3158 1198 (Carechem 24)
Indonesia: 007 803 011 0293 (Carechem 24)
Japan: 0120 015 230 (toll free) (Carechem 24)
Korea: +82 2 3479 8401 (Carechem 24)
Malaysia: +60 3 6207 4347 (Carechem 24)
New Zealand: +64 0800 803 002 (Allnex New Zealand)
Philippines: +63 2 231 2149 (Carechem 24)
Taiwan: +886 2 8793 3212 (Carechem 24)
Vietnam: +84 8 4458 2388 (Carechem 24)
All Others: +65 3158 1074 (Carechem 24)

Northern Asia

+44 (0) 1235 239 670 (Carechem 24)

Europe

+44 (0) 1235 239 671 (Carechem 24)

Latin America

Brazil: +55-800-707-7022 (toll free) or +55-11-98149-0850 (Suatrans 24)
Chile: +56 2 2582 9336 (Carechem 24)
Mexico and all others: +52-555-004-8763 (Carechem 24)

Prepared By: Product Sustainability & Regulatory Affairs Department, <http://www.allnex.com/contact>

This information is given without any warranty or representation. We do not assume any legal responsibility for same, nor do we give permission, inducement, or recommendation to practice any patented invention without a license. It is offered solely for your consideration, investigation, and verification. Before using any product, read its label.
