





# ROYALE BLACK® PP805B

### PRODUCT PROFILE

PP805B is a general-purpose low colour specialty pigment black suitable for a broad range of tinting and demanding moderate weathering in plastics applications.

Its morphology enables relatively high loadings in the masterbatches lowering formulation cost and its relatively larger particle size, help to disperse easily.

Key performance features are low sieve residue, better dispersion and low filter pressure value as compared to incumbent ASTM reference grades of SRF family.

PP805B is recommended all general-purpose master batch, as opacifying agent for film applications requiring moderate weatherability, utility pipes, irrigation pipe, and different kind of injection moulded goods applications.

## **TYPICAL VALUE**

NSA	STSA	OAN	Tint Strength	Sieve Residue	Heating Loss
m²/g	m²/g	cc/100g	% ITRB	325M, ppm	(As Shipped) %
30	28	65	60	40	0.5

# APPLICATION FIELD

TYPICAL APPLICATION RECOMMENDED DOSAGE

**Drip Irrigation Pipe System** 

Injection Moulded Goods 50%

LDPE Films >40 Micron Thickness

- · Recommended dosage can vary depending upon end use and modification of other ingredients
- Packaging 25kg paper bag or 500/1000kg bulk bag

### **PCBL Limited**

Registered Office: 31 Netaji Subhas Road, Kolkata - 700 001, WB, India
Corporate Office: RPSG House, 4th Floor, 2/4 Judges Court Road, Kolkata - 700 027, WB, India
P: +91 33 6625 1443 | F: +91 33 2248 0140/2243 6681 | W: www.pcblltd.com | E: pcbl.specialtyblack@rpsg.in

Revision No. - 01 Issue - Mar. 2023





